

Cable

SUPER STRONG ADHESIVE

TECHNICAL DATA SHEET

SMART ADVANTAGES

- DRIES CLEAR
- QUICK DRYING FOR FAST REPAIRS
- NON-DRIP

DESCRIPTION

Bostik Cable Adhesive is a clear, strong, quick drying adhesive, ideal for the gluing of PVC security, television and general electronic cabling to walls and ceilings.

APPLICATIONS

- Ideal for sticking all types of cables to walls and ceilings.
- General purpose fast drying clear glue.

ADHESION

Excellent adhesion to wide variety of materials i.e. acrylic paint, glass, cement, concrete, plaster, leather, felt, rubber, glass, metal, wood, and some plastics such as PVC and Perspex.

LIMITATIONS

- Not suitable for use on some plastics like polyethylene and polypropylene.
- If bonding a large surface area, ensure that at least one of the two surfaces are porous.
- May discolour when used outdoors.

SAFETY INSTRUCTIONS

Bostik Cable Adhesive is flammable. Always work in a ventilated area. Do not breathe in vapours. Avoid exposing product to any ignition sources. Do not smoke when working with Bostik Cable Adhesive. It is advisable to wear gloves in order to avoid direct contact with the skin. If product comes in to contact with skin or eyes, rinse thoroughly and immediately with water. Seek medical attention if irritation or discomfort persists. Keep out of reach of children! Refer to our Safety Data Sheets for further toxicological information and comprehensive handling instructions.

SURFACE PREPARATION

Ensure surfaces are clean, dry and free of loose materials, dust, grease, rust and other contaminants. Surfaces such as metals and glass should be degreased with a solvent e.g. acetone. Plastics should be lightly abraded with emery paper.

HOW TO USE

1. Ensure surfaces are prepared as above.
2. Apply adhesive to surface and push cable into the glue line.
3. Separate until the adhesive becomes tacky (approx. 60 seconds) and press firmly together.
4. Full cure after 30 – 60 minutes depending on amount of adhesive applied.

CLEANING

Clean with a suitable solvent, i.e. acetone or thinners, immediately after use.



STORAGE STABILITY

Bostik Cable Adhesive has a shelf life of 12 months if stored in a safe, cool (below 25°C), and dry place in its original moisture tight container. If the material is kept beyond the recommended shelf life, it is not necessarily unusable, but a check should be performed to observe whether the product is still workable.

PRODUCT PACKAGING

- 50ml Tubes

PRODUCT CHARACTERISTICS

Appearance	Clear viscous liquid
Solids (%)	34%
Viscosity	28000 – 38000 cPs

TYPICAL PERFORMANCE DATA

Chemical resistance	Good for intermittent contact with alcohol, oil, petrol diesel resistance. Poor resistance to esters and ketones.
Cold resistance	-10°C
Heat resistance	70°C
Water resistance	Waterproof
Skin over time	30 seconds
Drying time	30 – 60 minutes

DISCLAIMER

The above information is only offered as a guide to the use of this product. Furthermore, users should satisfy themselves that it is suitable for their needs. Since we have no control over the conditions under which it is used, we cannot accept responsibility for the problems caused by the use and/or application of this product.

Head Office: +27(0)21 555 7400
 Beverley Close, Montague Gardens, 7441
 PO Box 37008, Chempet, 7442
www.bostik.com/southafrica

ASK A STICKY QUESTION...

www.stickyquestions.co.za

0800 222 400

