

BOSTIK HARD PLASTICS CLEAR GLUE
Revision Number 1.02Revision date 27-May-2020
Supersedes Date: 18-May-2020**Section 1: Identification: Product identifier and chemical identity****Product identifier****Product Name** BOSTIK HARD PLASTICS CLEAR GLUE**Product Code(s)**
30803651
30617805; 30803651**Other means of identification****Proper Shipping Name** Adhesives**UN Number** UN1133**Pure substance/mixture** Mixture**Recommended use of the chemical and restrictions on use****Recommended use** Adhesive This product is a cyanoacrylate-based adhesive**Uses advised against** No information available**Details of manufacturer or importer****Supplier**Bostik Australia Pty Ltd
51-71 High Street,
Thomastown Victoria
Australia
Tel: 613 9279-9333
Fax: 613 9279-9342**Manufacturer**Bostik Limited
Common Rd
ST16 3EH
Stafford UK
Tel: +44 (1785) 27 26 25
Fax: +44 (1785) 25 72 36**ABN:** 79 003 893 838**E-mail address** au-bostik-sds@bostik.com**Emergency telephone number**

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification**GHS Classification**

Based on available information, this material is classified as hazardous according to criteria of Safe Work Australia

Flammable liquids	Category 2 - (H225)
Serious eye damage/eye irritation	Category 2A - (H319)
Specific target organ toxicity (single exposure)	Category 3 - (H336)

Label elementsFlame
Exclamation mark

SAFETY DATA SHEET

BOSTIK HARD PLASTICS CLEAR GLUE
Revision Number 1.02

Revision date 27-May-2020
Supersedes Date: 18-May-2020



Signal word
Danger

Hazard statements

H225 - Highly flammable liquid and vapor
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness
AUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements - Prevention

P264 - Wash face, hands and any exposed skin thoroughly after handling
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P271 - Use only outdoors or in a well-ventilated area
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P235 - Keep cool
P241 - Use explosion-proof electrical/ ventilating/ lighting/ equipment
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337 + P313 - If eye irritation persists: Get medical advice/attention
P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P312 - Call a POISON CENTER or doctor/physician if you feel unwell
P370 + P378 - In case of fire: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up

Precautionary Statements - Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other hazards which do not result in classification

May be harmful if swallowed
In use may form flammable/explosive vapor-air mixture
Will bond to skin
Polymerizes with evolution of heat

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number S5

Label requirements in accordance with SUSMP

CAUTION
KEEP OUT OF REACH OF CHILDREN
READ SAFETY DIRECTIONS BEFORE OPENING OR USING

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

SAFETY DATA SHEET

BOSTIK HARD PLASTICS CLEAR GLUE
Revision Number 1.02

Revision date 27-May-2020
Supersedes Date: 18-May-2020

Not applicable

Mixture

Chemical name	CAS No	Weight-%
Methyl ethyl ketone	78-93-3	>60
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	25068-38-6	< 1 %
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26
Poisons Information Center, New Zealand: 0800 764 766

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Clean mouth with water. Drink 1 or 2 glasses of water. Call a physician or poison control center immediately.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms Burning sensation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: Firefighting measures

Suitable extinguishing media

Suitable extinguishing media Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media Do not use straight streams. CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Specific hazards arising from the Risk of ignition. Keep product and empty container away from heat and sources of

SAFETY DATA SHEET

BOSTIK HARD PLASTICS CLEAR GLUE
Revision Number 1.02

Revision date 27-May-2020
Supersedes Date: 18-May-2020

chemical ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products Carbon oxides.

Special protective actions for fire-fighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Hazchem code •3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow to enter into soil/subsoil.

Methods and material for containment and cleaning up

Methods for containment Dike far ahead of spill; use dry sand to contain the flow of material. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Take up mechanically, placing in appropriate containers for disposal.

Precautions to prevent secondary hazards

Prevention of secondary hazards Eliminate all ignition sources if safe to do so.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

SAFETY DATA SHEET

BOSTIK HARD PLASTICS CLEAR GLUE
Revision Number 1.02

Revision date 27-May-2020
Supersedes Date: 18-May-2020

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations.

Incompatible materials None known based on information supplied.

This material is a scheduled poison and must be stored, maintained and used in accordance with the relevant regulations

Section 8: Exposure controls and personal protection

Control parameters

Exposure Limits

Chemical name	Australia
Methyl ethyl ketone 78-93-3	150 ppm TWA 445 mg/m ³ TWA 300 ppm STEL 890 mg/m ³ STEL

OEL as published by Safe Work Australia

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Hand protection Wear suitable gloves. Impervious gloves.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required. Organic gases and vapors filter conforming to EN 14387

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid
Appearance Liquid
Color Colorless
Odor Characteristic
Odor threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	
Melting point / freezing point	No data available	

SAFETY DATA SHEET

BOSTIK HARD PLASTICS CLEAR GLUE
Revision Number 1.02

Revision date 27-May-2020
Supersedes Date: 18-May-2020

Boiling point / boiling range	79 °C	
Flash point	-9 °C	
Evaporation rate	No data available	
Flammability (solid, gas)	Not applicable for liquids .	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	
Vapor density	No data available	
Relative density	No data available	
Water solubility	No data available	Polymerization can occur
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Hyphen	No data available	
Kinematic viscosity	30800 mm ² /s	@ 20 °C
Dynamic viscosity	No data available	
Explosive properties	No information available	
Oxidizing properties	No information available	
Other information		
Solid content (%)	No information available	
VOC Content (%)	No information available	
Liquid Density	No information available	

Section 10: Stability and reactivity

Reactivity

Reactivity No information available.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks.

Incompatible materials

Incompatible materials None known based on information supplied.

Hazardous decomposition products

Hazardous decomposition products None known based on information supplied.

Section 11: Toxicological information

SAFETY DATA SHEET

BOSTIK HARD PLASTICS CLEAR GLUE
Revision Number 1.02

Revision date 27-May-2020
Supersedes Date: 18-May-2020

Acute Toxicity

Information on likely routes of exposure

Product Information

Inhalation	May cause irritation of respiratory tract. May cause drowsiness or dizziness.
Eye contact	Causes serious eye irritation. May cause redness, itching, and pain.
Skin contact	May cause irritation. Prolonged contact may cause redness and irritation.
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Symptoms	May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document
ATEmix (oral) 3,154.80 mg/kg

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl ethyl ketone	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus cuniculus)	=11700 ppm (Rattus) 4 h
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	LD50 (Rattus) > 2000 mg/kg OECD 420	>2000 mg/Kg (Rattus)	-

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	May cause skin irritation.
Serious eye damage/eye irritation	Causes serious eye irritation.
Respiratory or skin sensitization	No information available.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.
Reproductive toxicity	No information available.
STOT - single exposure	May cause drowsiness or dizziness.
STOT - repeated exposure	No information available.
Aspiration hazard	No information available.

Section 12: Ecological information

Ecotoxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to	Crustacea
---------------	----------------------	------	-------------	-----------

SAFETY DATA SHEET

BOSTIK HARD PLASTICS CLEAR GLUE
Revision Number 1.02

Revision date 27-May-2020
Supersedes Date: 18-May-2020

			microorganisms	
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchneriella subcapitata)	LC50: 3130 - 3320mg/L (96h, Pimephales promelas)	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna)
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	EC50 (72h) = 9.4 mg/L (Scenedesmus capricornutum) EPA-660/3-75-009	1.2 mg/l 96Hr (Oncorhynchus mykiss)	-	2.7 mg/l 48hr Daphia Magna

Persistence and degradability

Persistence and degradability No information available.

Component Information			
Methyl ethyl ketone (78-93-3)			
Method	Exposure time	Value	Results
OECD Test No. 301D: Ready Biodegradability: Closed Bottle Test (TG 301 D)	28 days	biodegradation	98 % Readily biodegradable

Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Methyl ethyl ketone 78-93-3	0.3
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	3.26

Mobility

Mobility in soil No information available.

Mobility No information available.

Other Adverse Effects

Other adverse effects No information available.

Endocrine Disruptor Information

Chemical name	EU - Endocrine Disrupters Candidate List	EU - Endocrine Disrupters - Evaluated Substances	Endocrine disrupting potential
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	Group III Chemical	-	-

Section 13: Disposal considerations

Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

SAFETY DATA SHEET

BOSTIK HARD PLASTICS CLEAR GLUE
Revision Number 1.02

Revision date 27-May-2020
Supersedes Date: 18-May-2020

Section 14: Transport information

ADG

UN Number	UN1133
Proper shipping name	Adhesives
Hazard Class	3
Packing Group	II
Special Provisions	*
ADG Limited Quantity	5 L
Description	UN1133, Adhesives, 3, II
Hazchem code	•3Y

IATA

UN number	UN1133
Transport hazard class(es)	3
Packing group	II
ERG Code	3L
Special Provisions	A3
Limited Quantity (LQ)	1 L
Description	UN1133, Adhesives, 3, II

IMDG

UN number	UN1133
Transport hazard class(es)	3
Packing group	II
EmS-No	F-E, S-D
Limited Quantity (LQ)	5 L
Marine pollutant	Np
Description	UN1133, Adhesives, 3, II, (-9°C c.c.)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National Regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number S5

Major hazard (accident/incident planning) regulation

Verify that license requirements are met

Hazardous chemical

Liquids that meet the criteria for Class 3 Packing Group II or III
Liquids with flash points <61°C kept above their boiling points
at ambient conditions

Threshold quantity (T)

50 000
200

National pollutant inventory

Subject to reporting requirement

SAFETY DATA SHEET

BOSTIK HARD PLASTICS CLEAR GLUE
Revision Number 1.02

Revision date 27-May-2020
Supersedes Date: 18-May-2020

Chemical name	National pollutant inventory
Methyl ethyl ketone 78-93-3	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total

International Inventories

AICS	Listed
NZIoC	Not Listed
ENCS	Listed
IECSC	Listed
KECL	Listed
PICCS	Not Listed

Legend:

- AICS** - Australian Inventory of Chemical Substances
- NZIoC** - New Zealand Inventory of Chemicals
- ENCS** - Japan Existing and New Chemical Substances
- IECSC** - China Inventory of Existing Chemical Substances
- KECL** - Korean Existing and Evaluated Chemical Substances
- PICCS** - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

Revision date 27-May-2020

Revision note

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in

SAFETY DATA SHEET

BOSTIK HARD PLASTICS CLEAR GLUE
Revision Number 1.02

Revision date 27-May-2020
Supersedes Date: 18-May-2020

combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet