

BOSTIK NO MORE NAILS
Revision Number 3.01

Revision date 03-Jul-2020
Supersedes Date: 15-Mar-2019

Section 1: Identification: Product identifier and chemical identity

Product identifier

Product Name BOSTIK NO MORE NAILS

Product Code(s)

30607006
30603968; 30607005; 30607006; 30803249; 30804572; 30840373; 30840702

Other means of identification

Proper Shipping Name Adhesives

UN Number UN1133

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Adhesive

Uses advised against No information available

Details of manufacturer or importer

Supplier

Bostik Australia Pty Ltd
51-71 High Street,
Thomastown Victoria
Australia
Tel: 613 9279-9333
Fax: 613 9279-9342

Manufacturer

Bostik Australia Pty Ltd
51-71 High Street,
Thomastown Victoria
Australia
Tel: 613 9279-9333
Fax: 613 9279-9342

ABN: 79 003 893 838

ABN: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification

GHS Classification

Based on available information, this material is classified as hazardous according to criteria of Safe Work Australia

Flammable liquids	Category 2 - (H225)
Skin corrosion/irritation	Category 2 - (H315)
Specific target organ toxicity (single exposure)	Category 3 - (H336)

Label elements

Flame
Exclamation mark

SAFETY DATA SHEET

BOSTIK NO MORE NAILS
Revision Number 3.01

Revision date 03-Jul-2020
Supersedes Date: 15-Mar-2019



Signal word
Danger

Hazard statements

H225 - Highly flammable liquid and vapor
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness

Precautionary Statements - Prevention

P264 - Wash face, hands and any exposed skin thoroughly after handling
P280 - Wear protective gloves/protective clothing/eye protection/face protection
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
P271 - Use only outdoors or in a well-ventilated area
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P235 - Keep cool
P241 - Use explosion-proof electrical/ ventilating/ lighting/ equipment
P332 + P313 - If skin irritation occurs: Get medical advice/attention
P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
P363 - Wash contaminated clothing before reuse
P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P312 - Call a POISON CENTER or doctor/physician if you feel unwell
P370 + P378 - In case of fire: Use CO₂, dry chemical, or foam to extinguish

Precautionary Statements - Storage

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
P405 - Store locked up

Precautionary Statements - Disposal

P501 - Dispose of contents/ container to an approved waste disposal plant

Other hazards which do not result in classification

Toxic to aquatic life with long lasting effects
In use may form flammable/explosive vapor-air mixture

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number S5

Label requirements in accordance with SUSMP

CAUTION
KEEP OUT OF REACH OF CHILDREN
READ SAFETY DIRECTIONS BEFORE OPENING OR USING

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

Mixture

Australia - EN

SAFETY DATA SHEET

BOSTIK NO MORE NAILS
Revision Number 3.01

Revision date 03-Jul-2020
Supersedes Date: 15-Mar-2019

Chemical name	CAS No	Weight-%
Naphtha, petroleum, hydrotreated light, <0.1% Benzene	64742-49-0	10 - <30
Cyclohexane	110-82-7	0 - <10
Ethyl alcohol	64-17-5	0 - <10
Pentane	109-66-0	0 - <10
Hexane	110-54-3	0 - <10
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26
Poisons Information Center, New Zealand: 0800 764 766

Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Consult an ophthalmologist.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Get medical attention if irritation develops and persists.

Ingestion Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Clean mouth with water and drink afterwards plenty of water. Call a physician or poison control center immediately.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing.

Most important symptoms and effects, both acute and delayed

Symptoms Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

Section 5: Firefighting measures

Suitable extinguishing media

Suitable extinguishing media Dry chemical. Carbon dioxide (CO₂). Water spray. Alcohol resistant foam.

Unsuitable extinguishing media Do not use straight streams. CAUTION: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Specific hazards arising from the chemical Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated

SAFETY DATA SHEET

BOSTIK NO MORE NAILS
Revision Number 3.01

Revision date 03-Jul-2020
Supersedes Date: 15-Mar-2019

fire extinguishing water must be disposed of in accordance with local regulations.

Hazardous combustion products Carbon oxides.

Special protective actions for fire-fighters

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

Hazchem code •3Y

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas. Use personal protective equipment as required. Avoid contact with skin, eyes or clothing. Avoid breathing vapors or mists. Ensure adequate ventilation. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow to enter into soil/subsoil.

Methods and material for containment and cleaning up

Methods for containment Dike far ahead of spill; use dry sand to contain the flow of material. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Take up mechanically, placing in appropriate containers for disposal.

Precautions to prevent secondary hazards

Prevention of secondary hazards Eliminate all ignition sources if safe to do so.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. In case of insufficient ventilation, wear suitable respiratory equipment.

General hygiene considerations Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Wash hands before breaks and immediately after handling the product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wear suitable gloves and eye/face protection.

SAFETY DATA SHEET

BOSTIK NO MORE NAILS
Revision Number 3.01

Revision date 03-Jul-2020
Supersedes Date: 15-Mar-2019

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations.

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

This material is a scheduled poison and must be stored, maintained and used in accordance with the relevant regulations

Section 8: Exposure controls and personal protection

Control parameters

Exposure Limits

Chemical name	Australia
Cyclohexane 110-82-7	100 ppm TWA 350 mg/m ³ TWA 300 ppm STEL 1050 mg/m ³ STEL
Ethyl alcohol 64-17-5	1000 ppm TWA 1880 mg/m ³ TWA
Pentane 109-66-0	600 ppm TWA 1770 mg/m ³ TWA 750 ppm STEL 2210 mg/m ³ STEL
Hexane 110-54-3	20 ppm TWA 72 mg/m ³ TWA

OEL as published by Safe Work Australia

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron.
Antistatic boots.

Hand protection Wear suitable gloves. Impervious gloves.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
Organic gases and vapors filter conforming to EN 14387

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid
Appearance Very viscous Liquid

SAFETY DATA SHEET

BOSTIK NO MORE NAILS
Revision Number 3.01

Revision date 03-Jul-2020
Supersedes Date: 15-Mar-2019

Color light brown
Odor Solvent
Odor threshold No information available

Property	Values	Remarks • Method
pH	No data available	
Melting point / freezing point	No data available	
Boiling point / boiling range	70 °C	
Flash point	-10 °C	
Evaporation rate	No data available	
Flammability (solid, gas)	No data available	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	
Vapor density	No data available	
Relative density	1.16 - 1.18	None known
Water solubility	Insoluble in water	
Solubility(ies)	No data available	
Partition coefficient	No data available	
Autoignition temperature	No data available	
Decomposition temperature		
Kinematic viscosity	No data available	
Dynamic viscosity	272000 mPa s	
Explosive properties	No information available	
Oxidizing properties	No information available	
<u>Other information</u>		
Solid content (%)	No information available	
VOC Content (%)	< 300 g/L	
Density	No information available	

Section 10: Stability and reactivity

Reactivity

Reactivity No information available.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical impact None.
Sensitivity to static discharge Yes.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoid Heat, flames and sparks.

Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidizing agents.

SAFETY DATA SHEET

BOSTIK NO MORE NAILS
Revision Number 3.01

Revision date 03-Jul-2020
Supersedes Date: 15-Mar-2019

Hazardous decomposition products

Hazardous decomposition products None known based on information supplied.

Section 11: Toxicological information

Acute Toxicity

Information on likely routes of exposure

Product Information

Inhalation May cause irritation of respiratory tract. May cause drowsiness or dizziness.

Eye contact Irritating to eyes.

Skin contact Causes skin irritation.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms Redness. May cause redness and tearing of the eyes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 12,162.00 mg/kg mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Naphtha, petroleum, hydrotreated light, <0.1% Benzene	>5000 mg/kg (Rattus)	> 3160 mg/kg (Oryctolagus cuniculus)	=73680 ppm (Rattus) 4 h
Cyclohexane	=12705 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus cuniculus)	>9500 ppm (Rattus) 4 h
Ethyl alcohol	6200 - 15000 mg/kg (Rattus) OECD 401	-	=124.7 mg/L (Rattus) 4 h
Pentane	>2000 mg/kg (Rattus)	= 3000 mg/kg (Oryctolagus cuniculus)	=364 g/m ³ (Rattus) 4 h
Hexane	=25 g/kg (Rattus)	= 3000 mg/kg (Oryctolagus cuniculus)	=48000 ppm (Rattus) 4 h

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

SAFETY DATA SHEET

BOSTIK NO MORE NAILS
Revision Number 3.01

Revision date 03-Jul-2020
Supersedes Date: 15-Mar-2019

Chemical name	Australia
Naphtha, petroleum, hydrotreated light, <0.1% Benzene 64742-49-0	Carc. 1A

Reproductive toxicity No information available.

STOT - single exposure May cause drowsiness or dizziness.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

Section 12: Ecological information

Ecotoxicity

Ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Naphtha, petroleum, hydrotreated light, <0.1% Benzene 64742-49-0	-	LC50: =8.41mg/L (96h, Oncorhynchus mykiss)	-	LC50: =2.6mg/L (96h, Chaetogammarus marinus)
Cyclohexane 110-82-7	EC50 72 h > 9.3 mg/L (Pseudokirchnerella subcapitata)	LC50: 23.03 - 42.07mg/L (96h, Pimephales promelas) LC50: 48.87 - 68.76mg/L (96h, Poecilia reticulata) LC50: 3.96 - 5.18mg/L (96h, Pimephales promelas) LC50: 24.99 - 44.69mg/L (96h, Lepomis macrochirus)	EC50 = 85.5 mg/L 5 min EC50 = 93 mg/L 10 min	EC50: >400mg/L (24h, Daphnia magna)
Ethyl alcohol 64-17-5	EC50 72hr 12.9 g/l (Selenastrum capricornutum) NOEC 3.24 g/l (Skeletonema costatum)	LC50: >100mg/L (96h, Pimephales promelas)	EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min	LC50: (48h, Daphnia magna) EC50: =12.34 mg/L
Pentane 109-66-0	-	LC50: =11.59mg/L (96h, Pimephales promelas) LC50: =9.87mg/L (96h, Oncorhynchus mykiss) LC50: =9.99mg/L (96h, Lepomis macrochirus)	-	EC50: =9.74mg/L (48h, Daphnia magna)
Hexane 110-54-3	-	LC50: 2.1 - 2.98mg/L (96h, Pimephales promelas)	-	EC50: >1000mg/L (24h, Daphnia magna)

Persistence and degradability

Persistence and degradability No information available.

Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

SAFETY DATA SHEET

BOSTIK NO MORE NAILS
Revision Number 3.01

Revision date 03-Jul-2020
Supersedes Date: 15-Mar-2019

Chemical name	Partition coefficient
Cyclohexane 110-82-7	3.44
Ethyl alcohol 64-17-5	-0.32
Pentane 109-66-0	3.39

Mobility

Mobility in soil No information available.

Mobility No information available.

Other Adverse Effects

Other adverse effects No information available.

Endocrine Disruptor Information .

Section 13: Disposal considerations

Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.

Section 14: Transport information

ADG

UN Number UN1133
Proper shipping name Adhesives
Hazard Class 3
Packing Group III
Special Provisions 223, *
Description UN1133, Adhesives, 3, III

Hazchem code •3Y

IATA

UN number UN1133
Transport hazard class(es) 3
Packing group III
ERG Code 3L
Special Provisions A3
Limited Quantity (LQ) 10 L
Description UN1133, Adhesives, 3, III

IMDG

UN number UN1133
Transport hazard class(es) 3
Packing group III
EmS-No F-E, S-D
Limited Quantity (LQ) 5 L
Special Provisions 223, 955
Marine pollutant P.
Description UN1133, Adhesives (Cyclohexane), 3, III, (-10°C c.c.), Marine Pollutant

SAFETY DATA SHEET

BOSTIK NO MORE NAILS
Revision Number 3.01

Revision date 03-Jul-2020
Supersedes Date: 15-Mar-2019

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Australia

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Classified as a scheduled poison according to the Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

Poison Schedule Number S5

Major hazard (accident/incident planning) regulation

Verify that license requirements are met

Hazardous chemical

Liquids that meet the criteria for Class 3 Packing Group II or III
Liquids with flash points <61°C kept above their boiling points
at ambient conditions

Threshold quantity (T)

50 000

200

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Cyclohexane 110-82-7	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Ethyl alcohol 64-17-5	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Pentane 109-66-0	20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total
Hexane 110-54-3	10 tonne/yr Threshold category 1 20 MW Threshold category 2b total 60000 MWH Threshold category 2b total 1 tonne/h Threshold category 2a total 25 tonne/yr Threshold category 1a total 400 tonne/yr Threshold category 2a total 2000 tonne/yr Threshold category 2b total

International Inventories

AICS

Listed

SAFETY DATA SHEET

BOSTIK NO MORE NAILS
Revision Number 3.01

Revision date 03-Jul-2020
Supersedes Date: 15-Mar-2019

NZIoC	Listed
ENCS	Not Listed
IECSC	Listed
KECL	Not Listed
PICCS	Not Listed

Legend:

AICS - Australian Inventory of Chemical Substances
NZIoC - New Zealand Inventory of Chemicals
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

Revision date 03-Jul-2020

Revision note

The symbol (*) in the margin of this SDS indicates that this line has been revised.

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation
C	Carcinogen		

Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet