



Fast Tak Repositionable Spray

A SOLVENT BORNE REPOSITIONABLE CONTACT ADHESIVE SPRAY

Date: 13 August 2020

Fact Sheet No.: TDS00550

YOUR SMART ADVANTAGES

- Clear multipurpose spray adhesive
- Ideal for presentations, crafts, minor household repairs and spraying larger areas
- Good for bonding a variety of materials and mounting paper onto card

USES

Bostik Fast Tak Repositionable Spray is a pressure sensitive, solvent-borne spray adhesive based on synthetic rubber/resin. It has many craft and hobby uses where initial realignment may be required in order to ensure a good presentation. The adhesive does not contain any chlorinated or fluorinated compounds.

Suitable for bonding to most paper and cardboard, e.g. metallic foil, many rigid plastics, wood and wood derivatives, canvas and similar fabrics.

Quick and easy adhesive providing a clear and repositionable bond, useful in a wide range of crafts and hobbies.

PRODUCT CHARACTERISTICS

Colour	Transparent/Colourless
Form	Aerosol adhesive
Composition	Synthetic rubber
Product Code	30813297 150ml aerosol cans x 6
Storage/Shelf Life	Store for up to 24 months from date of manufacture when stored in original, unopened packaging under dry conditions within the temperature range of +5°C to +25°C.

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature	+15°C to +30°C Do not use below +5°C or above +40°C
Service Temperature	-15°C to +50°C
Coverage	150ml will generally provide 1.5m ² coverage applied to one surface, but is dependent on materials to be bonded and manner of application.
Drying Times	Typically a few minutes at 20°C to 25°C, but time depends on conditions of use, e.g. nature of the surface, amount of adhesive applied and ambient temperature.

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Fast Tak Repositionable Spray refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

1. Only use Bostik Fast Tak Repositionable Spray outdoors or in a well-ventilated area.
2. Work on a protected surface as any overspray is very difficult to remove, particularly from sensitive surfaces.
3. All surfaces to be bonded must be clean and dry, and dust free.
4. Shake the can thoroughly before use.

APPLICATION

5. Only apply the adhesive to the area to be bonded and to one surface only.
6. Spray Bostik Fast Tak Repositionable Spray 15 to 20cm (6 - 8 inches) away from the material to be bonded, avoiding overspray.

7. Allow the adhesive to dry for a few seconds and press both surfaces together.
8. To reposition carefully pull the surfaces apart, realign and press back together.
9. After use, always clear the nozzle by turning the can upside down and spraying away from you for a few seconds to prevent clogging.

CLEANING

10. For removal, clean with white spirit immediately after application.

PRECAUTIONS IN USE

Not intended for use as a structural adhesive and should not be used in safety critical applications, e.g. bearing overhead loads. Should not be used on surfaces or materials where the temperature can exceed 50°C. Not suitable for use with plasticized PVC or expanded polystyrene, polythene and polypropylene. Test before using on new or unfamiliar applications to confirm suitability before use. Use over a protected work surface. Avoid using near polished and some painted surfaces as the adhesive may spoil the finish. Take care to avoid heavy application which can cause strike-through on thin, absorbent materials. Accidental overspray can sometimes be removed using lighter fuel or white spirit. Care must be taken to avoid damaging delicate materials, e.g. by abrasion.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for Bostik Fast Tak Repositionable Spray, available at www.bostik.com/uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	sds.box-eu@bostik.com