

Fix & Flash

LIGHT-ACTIVATED METHOXYETHYL CYANOACRYLATE GLUE

Date: 30 March 2022

YOUR SMART ADVANTAGES

- Strong light-activated glue
- Repositionable until you shine the light to set the glue
- Works on almost all materials, even opaque ones

USES

Bostik Fix & Flash is an ultra strong, light-activated glue that sticks almost anything! It even works on opaque materials thanks to it's shadow curing technology, which allows the glue to dry from the edges into the core.

The glue does not set until you shine the light on it, so you can position and reposition your objects until you're happy. The light comes in the pack with the tube, so you're ready to bond or repair as soon as you like.

Bostik Fix & Flash is non-hazardous. It includes replaceable batteries (2 x CR2016). The tube has a fine nozzle, which allows a precise and clean application.

Bostik Fix & Flash works on most materials including porcelain, ceramics, glass, mirrors, leather, wood, paper, card, metal, fabrics, hard plastic, concrete, brick and much more.

PRODUCT CHARACTERISTICS		
	Straw yellow liquid that is transparent after drying/ Greenish if cured in a block (bulk)	
Specific Gravity	1.19 g/cm ³	

Fact Sheet No.: TDS02030

Composition	Methoxyethyl Cyanoacrylate		
Product Code	30619199 3g tube and light on blister card x 6		
	30613580 5g refill tube on blister card x 6		
Storage/Shelf Life	12 months in its sealed original packaging, stored at +20°C. Once opened, your product will keep for several months stored vertically away from light in a cool dry place. Protect from frost.		
Odour	Nil		
Viscosity	Medium		
TYPICAL PERFORMANCE DATA (Approx.)			
Open Time	<1 min		
Adjustment Time	Approx. 10 seconds*		
Drying Time (with direct light application)	Approx. 15 seconds**		
Full Cure	17 to 24 hours at 25°C*		
* These times can vary depending on the levels of			

* These times can vary depending on the levels of natural UV light in the room ** This time can vary depending on the thickness of the glue layer

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Fix & Flash refer to the relevant Health & Safety Data Sheet available at www.bostik.com/uk.

PREPARATION

- 1. The surfaces must be clean, dry and free from any dust and grease.
- 2. Before first use, screw the nozzle onto the tube and remove the cap to use.

APPLICATION

- Apply a small amount of glue to create a continuous bead of glue along the edges of the object.
- 4. You have time to reposition your objects before you shine the light to set the glue.
- 5. When you are happy with the position, switch on the light, then shine it around the edge for 15 seconds, moving it around to cover all areas.
- Once the glue is dry, you can sand it or paint it. Gently sand the edges of the glue until the desired effect is achieved. Then, with a fine paintbrush, paint the area you wish to cover.

CLEANING

7. Fresh Glue- Acetone Dry Glue- Sanding

PRECAUTIONS IN USE

Protect work surface.

Product will not work on polyolefins (eg. PP & PE) and silicone.

Product should not be eaten or used on body parts. Do not use for objects that hold hot food/liquids or highstress joints.

CAUTION: The LED lamp emits a small quantity of Ultra Violet radiation. Direct exposure to strong light can damage the eyes. Do not look directly at or point the light beam at someone's face or animals.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Fix & Flash, available at www.bostik.com/uk



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	<u>customer.service@bostik.com</u>
Technical Advice	Tel: 0844 371 1197	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	<u>sds.box-eu@bostik.com</u>